

RAKU BURNER SYSTEMS OPERATING INSTRUCTIONS

NOTE: BURNERS SHOULD BE INSTALLED IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL CODES, RULES, LAWS OR REGULATIONS. ONLY QUALIFIED PERSONNEL SHOULD INSTALL OR SERVICE BURNERS OR BURNER SYSTEMS. INSTALLATION PERMITS SHOULD BE OBTAINED FROM LOCAL ENFORCING AGENCY. USE CORRECT PRESSURE FOR THE BURNER AND BE SURE FLUE AND FIREBOX ARE OF PROPER SIZE BEFORE OPERATING.

PROPANE CONNECTIONS BETWEEN REGULATOR AND TANK ARE REVERSE THREADED. LEFT (COUNTERCLOCKWISE) IS TIGHT, RIGHT (CLOCKWISE) IS LOOSE.

1. Make sure burner ball valve is closed and primary air spin plate is open.
2. If burner is not equipped with BASO™ valve; proceed to step #6.
3. Hold flame to front of pilot while holding down the reset button on the BASO valve. Remember, the ball valve should be closed or gas will pass to the main burner. When pilot ignites, continue to hold down the reset button for 20-30 seconds. Release.
4. If pilot does not light, repeat step #3
5. Slowly open burner ball valve until the main burner ignites. Adjust to desired output.
6. For burners without BASO valve, Hold flame to tip of the burner and slowly open the ball valve until burner ignites. Adjust to desired output.
7. When firing is complete, shut off burner ball valve and tank valve.
8. **MR750 & MR100** Raku systems should use pressures in the 1-8 PSI range. The **B-3** Raku systems can use 1-20 PSI.

NOTE: USE LIGHTING WAND OR LONG MATCHES WHEN LIGHTING BURNERS. DO NOT USE BUTANE LIGHTERS OR SHORT MATCHES.

NOTE: High pressure BASO™ valves are rated for pressures up to 25 PSI. These valves cannot be used without a pressure regulator, nor should any device connected to a propane tank. These valves allow gas to pass to the main burner when the reset button is depressed. Make sure main burner ball valve is closed before lighting pilot burners.

NOTE: Regulators on Raku systems should be kept dry and free of dust and dirt. Since Raku involves the use of combustible materials, a water hose and fire extinguisher should be kept handy.

NOTE: Tank freezeup on propane fired Raku systems is a sign of gas withdrawal that is too rapid in relation to the tank size. If this is a problem, use a larger tank or slave a couple of tanks together.



PO BOX 1086 • DANDRIDGE, TN • 37725
PH: (865) 397-2914 FAX: (865) 397-1253

We will not be liable for any loss or damage that may arise in connection with the use or performance of any item, including, without limitation, any indirect or consequential damages.